



52700

Super Seal Smooth Patch
Technical Data Sheet

1 Gal Super Seal
Smooth Patch™

Item #: 52700
UPC #: 090832 52700 3

Section I - PHYSICAL PROPERTIES & PERFORMANCE

Appearance: Thick Brown Mixture dries black.	Maximum VOC: Less than 10 g/l
Application Temperature: 55° F and rising.	Specific Gravity: 1.3-1.5
Viscosity: 5,000-10,000 cps	Weight Per Gallon: 10.8-11.6 lbs. per gallon
Color: Brown	Consistency: Thick mixture
Boiling Point: >212° F	Cure Time (50% relative humidity, 70° F): 24-48 hours.
Freeze ability: Do not allow to freeze.	Container Size & Weight: 1 gallon pail, approx. 11.2 lbs. per pail

Section II – FEATURES

Super Seal Smooth Patch™ is a smooth asphalt repair product. It is designed to repair medium to large cracks, smooth out rough spots and fill minor depressions. **FEATURES:** Black, cement-like formula. For rough spots, depressions, low spots and medium/large cracks. EZ stir formula. Just trowel and smooth over troubled area. Allow to fully cure prior to sealing. Low VOC Formula.

Section III - SURFACE PREPARATION

Prior to using Super Seal Smooth Patch™ it is important to thoroughly clean the area. Sweep out any loose debris and rinse. Once the area is dry, you are ready to apply.

Section IV – APPLICATION

Super Seal Smooth Patch™ is designed to repair medium-sized cracks and to smooth out rough spots and minor depressions on asphalt driveways. Prior to using Super Seal Smooth Patch™ it is important to thoroughly clean the area. Sweep out any loose debris and rinse. Once the area is dry, you are ready to apply. Just trowel onto troubled area. Super Seal Smooth Patch™ dries from the top down so it is important not to apply it too thick. **We recommend applying no more than three ½" lifts consecutively.** If the depression or crack is deeper than ½", apply the first layer and let that set up and cure thoroughly prior to applying another layer. Once you finish applying, ensure that it is completely dried and cured prior to sealing.

Section V – PRECAUTIONS

Avoid applying when rainfall is likely within 24 hours of application time. Avoid applying when temperatures drop below 55° F. Allow all repaired surfaces to cure 24 hours prior to sealing. For crack fillers you should wait 24 hours. If the crack filler is firm you may seal over. When transporting this product, ensure that the container is secured and the lid is secure. Do not allow the container to tumble as this may loosen the lid and allow leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Protective clothing and eyewear should be used during application.

Section VI - CLEAN UP & STORAGE

Fresh crack filler will clean up with soap and water.

Section VII - !!!CAUTION!!!

Super Seal Smooth Patch™ is for exterior use only. Keep out of reach of children. Keep container capped when not in use. Non-flammable. This product contains chemicals known to the state of California to cause cancer and birth defect.

Emergency & First Aid Procedures:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Ingestion: DO NOT INDUCE VOMITTING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

Section VIII - WARRANTY AND DISCLAIMER

The methods and techniques described herein represent some that have been used successfully to obtain desired results. Allow new pavement to fully cure-we recommend a minimum of 12 months prior to sealing. If water "beads up" on pavement it has not fully cured. All variations in asphalt, climate conditions and equipment cannot be anticipated. The decision to use any of these methods and techniques is entirely at the election and responsibility of the user. Sealer is warranted from defects for a period stated on the pail from date of purchase when applied according to our application instructions. Since sealer cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Manufacturer disclaims liability for areas that are flat, have ponding waters, poor drainage or snow removal damage. If product is deemed defective, it shall be replaced. No warranties will apply if the goods are in any way altered or modified after delivery by seller. There are no express warranties which extend beyond the description on the face hereof, manufacturer disclaims any implied warranties. This warranty does not include labor costs incurred for the application, re-application or consequential damage costs. Failures due to acts of God, fire, structural defects or causes beyond our control are excluded from this warranty. If repair products were used, repair products must be used for warranty to be honored. Two coats must be applied to validate warranty. Not applicable on commercial parking lots. This warranty gives you specific rights and you may also have other rights which may vary from state to state. Original proof of purchase required for warranty claims.